



Inverter

- Precise and efficient TIG arc striking by high frequency
- Steady, easily targeted arc makes welding easy
- Low energy consumption and high efficiency
- Automatic compensation for mains voltage fluctuations within + %15 -%20
- Great voltage reserve increases ease of operation
- High performance on thin metal sheets
- Shock-proof fibre compound main structure
- Perform very well in MMA welding
- Single-Phase network
- Light weight and a compact size give better reach



		TIG	MMA
Input Voltage	V	1 Phase 220/230	50/60 Hz \pm %15
Installed Power	kVA	7.2	7.9
Fuse (delayed action)	A	16	16
Open Circuit Voltage	V	88	88
Current Range	A	5-170	5-150
Duty Cycle at (40°C)	%100	95	95
	%60	115	115
	%20	170	150 (%25)
Standards		EN 60974-1 / EN 60974-3 / EN 60974-10	
Protection Class	IP	23 S	
Insulation Class		F	
Dimensions ((L*W*H)	mm	390 / 135 / 300	
Weight	kg	7	

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

3021000000



1021000000



2020900723



6051900083



2020900723

GEDIK Welding provides full support for after sales services. 1 year warranty.