



- Compact type MIG/MAG welding machine, with wire feeding unit placed inside the machine
- Voltage calibration with 10 stages between 30-250 A welding current range
- High efficiency with 2 stage choke coil
- Ideal for welding sheet metals up to 4.0 mm
- Wire feeding speed adjustment within 1-23 mt/min range
- 2-4 trigger selection



Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	15.6
Fuse (delayed action)	A	32
Open Circuit Voltage	V	18-47
Current Range	A	30-350
Duty Cycle at (40°C)	%100 %60 %40	230 / 300 / 350
Standards		EN 60974-1 / EN 60974-5 / EN 60974-10 / S
Usable Wire Diameters	mm	0.8 / 1.0 / 1.2
Protection Class	IP	23
Insulation Class		H
Dimensions ((L*W*H)	mm	930 / 480 / 900
Weight	kg	125

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments



3000900005



3020900003



1051900011 (3mtr)



6051900028
(4mtr)
(Optional)



6011100078



1051300003
Argon



1051300015
CO₂

Please Select One



1051300016

GEDIK Welding provides full support for after sales services. 1 year warranty.