










- Compact type MIG/MAG welding machine, with the wire feeding unit placed inside the machine
- Voltage calibration with 18 stages between 30-420 a welding current range
- High efficiency with 2 stage choke coil
- Ideal for welding metal sheets up to 15 mm
- Wire feeding speed adjustment within 1-22 mt/min range.
- 2-4 trigger selection
- Digital current and voltage indicator



Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	17.5
Fuse (delayed action)	A	42
Open Circuit Voltage	V	13-43
Current Range	A	30-420
Duty Cycle at (40°C)	%100 %60 %45	280 / 360 / 420
Standards		<b>EN 60974-1 / EN 60974-5 / EN 60974-10 / S</b>
Usable Wire Diameters	Ø mm	0.8 / 1.0 / 1.2
Protection Class	IP	23
Insulation Class		H
Dimensions ((L*W*H)	mm	1075 / 500 / 800
Weight	kg	140

### STANDARD & OPTIONAL EQUIPMENTS

<p>This Order Code Covers The Welding Machine and All of The Equipments</p> 					<p>Please Select One</p> 		
3000900008	3020900020	1051900011 (3mt)	6051900028 (4mt) (Optional)	6011100078	1051300003 Argon	1051300015 CO <sub>2</sub>	1051300016

GEDIK Welding provides full support for after sales services. 1 year warranty.