

## Product Features

- Efficient use of every single inch with constant suction and filtration
- Easily traps and filters all kinds of fumes and volatile wastes with its high local extraction power
- Flexible and extendable extraction arms allow easy access
- Extraction arms of different lengths
- Features optional hepa filter
- Alerts to “clean the filter” when the air flow is insufficient
- Suitable for all welding processes with its durable and silent structure
- Its special design ensures maximum fire safety
- Operation lifetime ranging from 300 to 600 hours
- Fully consistent design with CE standards



## General Filter Data

Filtering Phase	3-phase
Filter Type	Disposable
Filter Surface Area	16 m <sup>2</sup>
Efficiency	>99%
Main Filter Surface	16 m <sup>2</sup>
Main Filter Class	F8
Phase 1 Filter	Washable Spark Trap
Phase 2 Filter	Replaceable Pre-Filter G4
Phase 3 Filter	Replaceable Main Filter F8

## Technical Details

Dimensions	650 x 750 x 1030 mm
Weight	105 kg (excluding arm)
Engine Output	1,1 kw
Power Supply	3 x 400 V/50 Hz
Noise Level	72 dB(A)
Current	2,7 A
Fan Type	Radial - Narrow Type With Rotor
Certification	CE
Main Filter Surface	-17 m <sup>3</sup>
Extraction Capacity	1300 m <sup>3</sup> /h
Main Filter Class	F8

## Standard and Optional Equipment

This order code includes the Main Unit and Standard 3m Arm / F8 and G4 Filters

605140022



2m 605140065  
3m 605140066  
4m 605140067



Main Filter (F8)  
605140002



Preliminary Filter (G4)  
605140028



HEPA Main Filter H13  
605140033  
(Opsiyonel)



HEPA Intermediary Filter F7  
605140034  
(Opsiyonel)