



- Maximum efficiency
- Designed for Heavy Industrial Use
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under  $\pm$  % 15 Energy fluctuations
- Hot Start/Arc Force/Anti Stick
- VRD Function (Optional)
- Lift-TIG available
- Thermal Protection
- Fail-safe protection
- Overcurrent Protection
- Overvoltage Protection
- Plastic front and rear panels
- Durable metal body
- Aesthetic design

**Inverter**



### PoWer ARC 405

Input Voltage	V	3 Phase 380V $\pm$ %10
Installed Power	kVA	18.1
Fuse (delayed action)	A	25
Open Circuit Voltage	V	100V VRD:4V
Current Range	A	15 - 400
Duty Cycle at (40°C)	%40 - %100	400 - 250
Standards	<b>EN ISO 60974-1, EN ISO 60974-10</b>	
Protection Class	IP	23
Insulation Class	H	
Dimensions (L*W*H)	mm	535 / 195 / 345
Weight	kg	16

### STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

3021000094



1021000059



2020900647



2020900648



6051900088  
(Optional)