



Product Features

Effective Working

- Able to operate with generators
- Designed for Heavy Industrial Use
- Less energy consumption (Cos Ø: 0,99)
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under $\pm 10\%$ voltage fluctuations
- Working with wide range of input voltage

Extra Functions

- 2T/4T Welding operation mode
- Selectable Past Flow time
- Down slope time adjustable
- Multi Purpose (HF TIG/MMA)

Protection Functions

- Thermal Protection
- Overcurrent Protection
- Overvoltage Protection

Design

- Plastic front and rear panels
- Durable metal body



Welding Process	Input Voltage (V)	Power Cons. (kVA)	Anma Girişi (A)	No Load Voltage (V)	Welding Current Range (A)	Duty Cycle(40°)			Standards	Protection	Isolation Class	Dimensions (DxWxH) (mm)	Weight (kg)
						%100	%60	%50					
TIG	1 Phase, 50/60 Hz, 220 \pm 10	4,4	20	66	5-200	145	180	200	EN ISO 60974-1	IP23	H	420 x 135 x 250	9
MMA		7	32			135	145	200 (%30)	EN ISO 60974-10				

Standard & Optional Equipments

<p>This order code covers the welding machine and all of the equipments</p> <p>3021000058</p>	 1021000037	 1051900000	 2020900723	 1051300003
--	--	--	--	---

GEDIK Welding provides full support for after sales services. 1 year warranty.