



Product Features

Effective Working

- Maximum efficiency
- Able to operate with generators
- Designed for Heavy Industrial Use
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under \pm % 10 Energy fluctuations

TIG Mode

- Lift-TIG available

Extra Functions

- Hot Start
- Arc Force
- Anti Stick
- VRD Function (Optional)

Protection Functions

- Thermal Protection
- Phase missing
- Overcurrent Protection
- Overvoltage Protection

Design

- Plastic front and rear panels
- Durable metal body



Input Voltage (V)	Power Cons. (kVA)	Delayed Fuse (A)	No Load Voltage (V)	Welding Current Range (A)	Duty Cycle(40°)		Standards	Protection	Isolation Class	Dimensions (DxWxH) (mm)	Weight (kg)
					%100	%60					
3 Phase, 50/60 Hz, 380/440 V	16,4	16	55	10-320	240	320	EN ISO 60974-1 EN ISO 60974-10	IP23	H	485 x 240 x 445	17

Standard & Optional Equipments

This order code covers the welding machine and all of the equipments

302100093



102100058



2020900647



2020900648



6051900088 (Optional)

Perfect welding capability for all types of electrodes with \varnothing 2,0 - 5,0 mm diameter. GEDIK WELDING provides full support for after sales services. 1 year warranty.