



Inverter

- Suitable for all weldable materials and all types of current
- Precise and efficient TIG arc striking by high frequency
- Standard equipped with pulse mode integrated into the control with available "easy-pulse" facility
- Low energy consumption and high efficiency
- Automatic compensation for mains voltage fluctuations within + %15 - %20
- High performance on thin metal sheets
- Very good MMA welding characteristics with any type of electrodes
- Single - Phase network



PoWer TIG 2200 AC / DC Pulse		TIG	MMA
Input Voltage	V	1 Phase, 50/60 Hz, 220 V	
Installed Power	kVA	5.4	6.3
Fuse (delayed action)	A	16	16
Open Circuit Voltage	V	100	100
Current Range	A	5-220	5-180
Duty Cycle at (40°C)	%100	140	120
	%60	180	150
	%30	220	180
Standards		EN 60974-1 / EN 60974-3 / EN 60974-10	
Protection Class	IP	23 S	
Insulation Class		H	
Dimensions (L*W*H)	mm	465 / 185 / 390	
Weight	kg	15.5	

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments 3021000014 Air Cooled 3021000015 Water Cooled									
	1021000008	6051900083	2020900723	1051300003	1024300005 (Optional)	2020900179 (Optional)	6051900076 (Optional)	6051300053 (Optional)	6051300012 (Optional)

GEDİK Welding provides full support for after sales services. 1 year warranty.