



- Possible to weld with all electrodes up to  $\varnothing$  6.0 mm
- Possible to weld with cutting and gouging electrodes with  $\varnothing$  6.0 -  $\varnothing$  10.0 mm
- Current adjustment using potentiometer with thyristor control
- Digital current and voltage indicators
- Fan-cooling system and thermic protection
- Strong and durable enough to work under difficult and heavy conditions
- LIFT-TIG available
- Remote control available



Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	39
Fuse (delayed action)	A	63
Open Circuit Voltage	V	82
Current Range	A	50-650
Duty Cycle at (40°C)	%100 %60 %35	390 / 500 / 650
Standards	<b>EN 60974-1 / EN 60974-10</b>	
Protection Class	IP	23
Insulation Class	H	
Dimensions ((L*W*H)	mm	980 / 760 / 660
Weight	kg	265

### STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

3000900017



3020900109



2020900662



2020900661



6051900088  
(Optional)



6051900107  
(1000 A)  
6051900108  
(1250 A)  
(Optional)



1000900012  
(Optional)

GEDIK Welding provides full support for after sales services. 1 year warranty.