



Inverter

- Standard equipped with pulse mode integrated into the control with available "EASY PULSE" facility
- Precise and efficient TIG arc striking by high frequency
- Steady, easily targeted arc makes welding easy
- Low energy consumption and high efficiency
- Automatic compensation for mains voltage fluctuations within +%15 -%20, great voltage reserve increases ease of operation
- Digital control of all the welding parameters with the ability to store 9 personalised programs
- High performance on thin metal sheets
- Cycle and Pulse Functions improve welding productivity
- Perform very well in MMA welding, single - Phase network
- Light weight and a compact size give better reach



		TIG	MMA
Input Voltage	V	1 Phase 50/60 Hz, 230 V	
Installed Power	kVA	8.5	9.0
Fuse (delayed action)	A	20	20
Open Circuit Voltage	V	88	88
Current Range	A	5-200	5-160
Duty Cycle at (40°C)	%100	120	110
	%60	140	130
	%25	200	160 (%30)
Standards		EN 60974-1 / EN 60974-3 / EN 60974-10	
Protection Class	IP	23 S	
Insulation Class		F	
Dimensions ((L*W*H)	mm	390 / 135 / 300	
Weight	kg	7.5	

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

302100001



102100001



2020900723



6051900083



1051300003

GEDIK Welding provides full support for after sales services. 1 year warranty.