

## PoWer MIG GS WB 400



- MIG- MAG / MMA (Electric Are Welding) / TIG-Lift (Argon) multiprocess functions
- Excellent software optimized for coated materials such as galvanized.
- Memory function for 100 parameters
- Easy to adjust parameters such as pre-gas / post-gas, up-slope / down-slope, initial current / final current, crater filling - are spot time etc
- When the stick out is changable and long, constant function eliminate the disadvantages
- Newly developed tunnel protection and due to the revolution control of cooling fan according to its duty cycle or ambient air temperature, the design prevents dust from entering the area where electronic components are installed
- Data editing / copying / transferring, using USB via machine front panel
- Unique wire feeding advantages via three wire straighteners and four feed rollers
- Interface board is located in the machine as a standart, which provides an easy connection to PLC, Automation & Robotic Systems
- Ease of control of the machine current using a standard torch without the need for high-cost torches with special control
- Optionally, monitoring of welding data from android mobile phone. tablet or PC, graphical welder test, amount of wire consumption. working time, recording of WPS work and print out etc. Technologieal advantages



















Input Voltage	V	3 Phase, 50/60 Hz, 400 ± 15 V	
Installed Power	kVA	17.7	
Fuse (delayed action)	Α	25	
Open Circuit Voltage	V	70	
Current Range	Α	30-400	
Current Tension Range	V	12-34	
Duty Cycle at (40°C)	%50	400	
Standards		EN 60974-1 / EN 60974-5 / EN 60974-10 / S	
Protection Class	IP	23	
Insulation Class		Н	
Dimensions ((L*W*H)	mm	395 / 710 / 592	
Weight	kg	62	

WIRE FEEDER UNIT			
Wire Feeder Units		CM-7403A-D	
WireTypes		Fe / FC	Aluminum
Usable Wire Diameters	Ø mm	0.8/0.9/1.0/1.2/1.4/1.6	1.0/1.2/1 .6
Wire Feeding Speed	mt/min.	22 max.	
Dimensions ((L*W*H)	mm	710 / 240 / 395	
Weight	ka	17	

## STANDARD & OPTIONAL EQUIPMENTS

























GEDİK Welding provides full support for after sales services. 1 year warranty.



(Optional) (Optional)