




- Compact type MIG/MAG welding machine, with wire feeding unit placed inside the machine
- Voltage calibration with 10 stages between 30-240 A welding current range
- High efficiency with 2 stage choke coil.
- Ideal for welding metal sheets up to 4.0 mm
- Wire feeding speed adjustment with 1-22 mt/min range.
- 2-4 trigger selection



Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	8
Fuse (delayed action)	A	32
Open Circuit Voltage	V	12-32
Current Range	A	30-240
Duty Cycle at (40°C)	%100 %60 %35	140 / 180 / 240
Standards		<b>EN 60974-1 / EN 60974-10</b>
Protection Class	IP	23
Insulation Class		H
Dimensions ((L*W*H)	mm	800 / 420 / 670
Weight	kg	82

### STANDARD & OPTIONAL EQUIPMENTS

<p>This Order Code Covers The Welding Machine and All of The Equipments</p> 						
3000900002	3020900001	1051900010 (3mt)	6051900022 (4mt) (Optional)	2020900697	<p>Please Select One</p> <p>1051300003 Argon</p> <p>1051300015 CO<sub>2</sub></p>	1051300016

GEDIK Welding provides full support for after sales services. 1 year warranty.