



- Water cooled MIG/MAG welding machine, which gives easy access to the work area by separating the wire teeding unit
- Voltage calibration with 36 (4x9) stages between 40-600 A welding current range
- Wire teeding system with 4 rolls
- High efficiency with 4 stage choke coil
- Ideal for welding metal sheets up to 50 mm
- It is preferred by heavy industrial companies
- Wire teeding speed adjustment within 1-22 mt/min range
- 2-4 trigger selection
- Digital current and voltage indicator










Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	33.6
Fuse (delayed action)	A	63
Open Circuit Voltage	V	18-60
Current Range	A	40-600
Duty Cycle at (40°C)	%100 %60 %45	410 / 520 / 600
Standards		EN 60974-1 / EN 60974-5 / EN 60974-10 / S
Protection Class	IP	23
Insulation Class		H
Dimensions ((L*W*H)	mm	1100 / 510 / 1440
Weight	kg	265

WIRE FEEDER UNIT

Usable Wire Diameters	Ø mm	0.8 / 1.0 / 1.2 / 1.6
Wire Types		Fe / FC
Wire Feeding Speed	mt/min	22 max
Dimensions ((L*W*H)	mm	630 / 460 / 230
Weight	kg	15

STANDARD & OPTIONAL EQUIPMENTS

<p>This Order Code Covers The Welding Machine and All of The Equipments</p> <p>3000900013</p>	 <p>3020900077</p>	 <p>1051900012 (3mt)</p>	 <p>6051900040 (4mt) (Optional)</p>	 <p>2020900660</p>	 <p>Please Select One 1051300003 Argon 1051300015 CO₂</p>	 <p>1051300016</p>	 <p>2020900258/5 mt 2020900259/10 mt (Optional) 2000200661/15mt (Optional)</p>
---	---	---	--	---	---	---	---

GEDIK Welding provides full support for after sales services. 1 year warranty.