



- Compact size and light weight
- Instantaneous arc starts and stable arc
- User friendly operations
- Cope with dust and sudden rain
- Light weight and compact size
- Automatic compensation for mains voltage fluctuations within  $\pm 15\%$
- Perform very well in MMA welding
- 3 phase network
- Current increase and decrease by single / double clicking of the standard torch switch
- Pulse welding allows a better arc control and less deformation of the work piece (0,1-500 Hz)
- Personalised welding program starting and recoiling

**Inverter**



PoWer TIG 300 DC Pulse		TIG	MMA
Input Voltage	V	3 Phase 50/60 Hz, 400 V $\pm 15$	
Installed Power	kVA	11	9
Fuse (delayed action)	A	32	32
Open Circuit Voltage	V	58	58
Current Range	A	4-300	10-250
Duty Cycle at (40°C)	%100	190	158
	%60	245	204
	%30	300	250
Standards	EN 60974-1 / EN 60974-3 / EN 60974-10		
Protection Class	IP	23 S	
Insulation Class	H		
Dimensions (L*W*H)	mm	640 / 250 / 370	
Weight	kg	30	

## STANDARD & OPTIONAL EQUIPMENTS

<p>This Order Code Covers The Welding Machine and All of The Equipments</p> <p><b>3021000008</b> Air Cooled</p> <p><b>3021000009</b> Water Cooled</p>	 <p><b>1021000005</b></p>	 <p><b>6051900083</b></p>	 <p><b>2020900649</b></p>	 <p><b>1051300003</b></p>	 <p><b>2020900175</b> (Optional)</p>	 <p><b>1024300000</b> (Optional)</p>	 <p><b>6051900076</b> (Optional)</p>
---	--	--	--	--	---	---	---

GEDİK Welding provides full support for after sales services. 1 year warranty.