



- Gas cooled MIG/MAG welding machine, which provides easy access to the work area by separating wire feed unit
- Voltage calibration with 12 stages between 30-350 a welding current range
- Wire feeding unit with 4 rolls
- High efficiency with 2 stage choke coil
- Ideal for welding sheet metals up to 8.0 mm.
- Wire feeding speed adjustment within 1-22 mt/min range
- 2-4 trigger selection
- Digital current and voltage indicator



GKM 350-2G

Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	16
Fuse (delayed action)	A	32
Open Circuit Voltage	V	13-45
Current Range	A	30-350
Duty Cycle at (40°C)	%100 %60 %40	210 / 270 / 350
Standards		EN 60974-1 / EN 60974-5 / EN 60974-10 / S
Protection Class	IP	23
Insulation Class		H
Dimensions (L*W*H)	mm	1075 / 500 / 800
Weight	kg	125
Weight	kg	75

WIRE FEEDER UNIT

Usable Wire Diameters	Ø mm	0.8 / 1.0 / 1.2
Wire Types		Fe / FC
Wire Feeding Speed	mt/min	22 max
Dimensions (L*W*H)	mm	630 / 460 / 230
Weight	kg	15

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

3000900004



3020900005



1051900011
(3mt)



6051900028
(4mt) (Optional)



6011100078



1051300003
Argon



Please Select One
1051300015
CO₂



1051300016



2020900244/5mt
2020900254/10mt
(Optional)
2020900275/15mt
(Optional)

GEDİK Welding provides full support for after sales services. 1 year warranty.