



- Compact type MIG/MAG welding machine, with wire feeding unit placed inside the machine
- Voltage calibration with 12 stages between 30-350 A welding current range
- High efficiency with 2 stage choke coil
- Ideal for welding metal sheets up to 8.0 mm
- Wire feeding speed adjustment within 1-22 mt/min range
- 2-4 trigger selection
- Digital current and voltage indicator



GKM 350-G		
Input Voltage	V	3 Phase, 50/60 Hz, 380 V
Installed Power	kVA	15.6
Fuse (delayed action)	A	32
Open Circuit Voltage	V	18-47
Current Range	A	30-350
Duty Cycle at (40°C)	%100 %60 %40	230 / 300 / 350
Standards		EN 60974-1 / EN 60974-5 / EN 60974-10 / S 0.8 / 1.0 / 1.2
Usable Wire Diameters	mm	23
Protection Class	IP	H
Insulation Class		930 / 480 / 900
Dimensions (L*W*H)	mm	125
Weight	kg	75

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

							
3000900005	3020900003	1051900011 (3mt)	6051900028 (4mt) (Optional)	6011100078	1051300003 Argon	1051300015 CO ₂	1051300016

Please Select One

GEDİK Welding provides full support for after sales services. 1 year warranty.