



## **General Filter Data**

| Filtering Phase     | 4-phase                          |
|---------------------|----------------------------------|
| Filter Type         | Disposable Cartridge             |
| Filter Surface Area | 16 m²                            |
| Main Filter Surface | 17 m²                            |
| Efficiency          | > 99%                            |
| Phase 1 Filter      | Mesh Spark Trap                  |
| Phase 2 Filter      | G4 Pre-filter                    |
| Phase 3 Filter      | F8 Main Filter 16 m <sup>2</sup> |
| Phase 4 Filter      | Granular Activated Carbon        |

## **Product Features**

- Our portable extraction and filtering devices allow you to efficiently use every single inch in your workshop.
- You can perform all kinds of welding and manufacturing operations without being tied to a particular spot in your workshop.
- You can easily capture and filter all kinds of odor, fume and volatile wastes thanks to our high-quality devices equipped with high local extraction power.
- With its flexible and extendable extraction arms, you can reach anywhere and easily provide extraction.
- Flexible extraction arms are available in various lengths of 2m, 3m and 4m with an inside diameter of 152mm.
- The extracted air goes through the flame trap first and then the pre-filter (G4) where it is separated from large and flammable particles. Later, the intake air that reaches the main filter is filtered at a rate of 99.0% and passes through the active carbon filter. Here, it is cleaned of its odor and returned to the environment where the extraction unit is located. This way, it provides significant energy savings without disturbance to the air conditioning in its environment.
- With its durable and silent structure it is compatible with all welding processes, particularly the TIG/MIG welding types.

## **Technical Details**

| Dimensions (WxDxH)     | 650 x 720 x 1285 mm              |
|------------------------|----------------------------------|
| Weight (Excluding Arm) | 131 kg                           |
| Acrobat Arm Diameter   | Ø152mm                           |
| Engine Output          | 1.5 kW                           |
| Supply voltage         | 3x400V/50Hz                      |
| Noise level            | 72 dB                            |
| Extraction capacity    | 1300 m³/h                        |
| Current                | 3 A                              |
| Fan Type               | Radial - Wide Type With<br>Rotor |

## **Standard and Optional Equipment**

This order code includes the Main Unit, Standard 3-m-Arm/ Mesh filter, G4 pre-filter, F8 main filter and carbon filter

6051400080





F8 Main Filter 6051400002



Preliminary Filter (G4) 6051400028



Activated Carbon Filter 6051400082