



- Maximum efficiency
- Designed for Heavy Industrial Use
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under  $\pm$  % 15 Energy fluctuations
- Hot Start/Arc Force/Anti Stick
- VRD Function (Optional)
- Lift-TIG available
- Thermal Protection
- Fail-safe protection
- Overcurrent Protection
- Overvoltage Protection
- Plastic front and rear panels
- Durable metal body
- Aesthetic design

**Inverter**



|                       |            |                                 |
|-----------------------|------------|---------------------------------|
| Input Voltage         | V          | 3 Phase 380V $\pm$ %10          |
| Installed Power       | kW         | 12.9                            |
| Fuse (delayed action) | A          | 25                              |
| No Load Voltage       | V          | 65V VRD:4V                      |
| Current Range         | A          | 15 - 300                        |
| Duty Cycle at (40°C)  | %40 - %100 | 300 - 240                       |
| Standards             |            | <b>EN 60974-1 / EN 60974-10</b> |
| Protection Class      | IP         | 21S                             |
| Insulation Class      |            | H                               |
| Dimensions (L*W*H)    | mm         | 435 / 195 / 345                 |
| Weight                | kg         | 13,5                            |

**STANDARD & OPTIONAL EQUIPMENTS**

|  |  |  |   |   |
|--|--|--|---|---|
| <p>This Order Code Covers The Welding Machine and All of The Equipments</p> <p><b>3000900032</b></p> |  <p><b>3020900167</b></p> |  <p><b>2020900647</b></p> |  <p><b>2020900648</b></p> |  <p><b>6051900088</b><br/>(Optional)</p> |
|--|--|--|---|---|