



- Maximum efficiency
- Designed for Heavy Industrial Use
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under \pm % 15 Energy fluctuations
- Hot Start/Arc Force/Anti Stick
- VRD Function (Optional)
- Lift-TIG available
- Thermal Protection
- Fail-safe protection
- Overcurrent Protection
- Overvoltage Protection
- Plastic front and rear panels
- Durable metal body
- Aesthetic design

Inverter



Input Voltage	V	3 Phase 380V \pm %10
Installed Power	kW	18.1
Fuse (delayed action)	A	25
No Load Voltage	V	100V VRD:4V
Current Range	A	15 - 400
Duty Cycle at (40°C)	%40 - %100	400 - 250
Standards		EN 60974-1 / EN 60974-10
Protection Class	IP	21S
Insulation Class		H
Dimensions (L*W*H)	mm	535 / 195 / 345
Weight	kg	16

STANDARD & OPTIONAL EQUIPMENTS

<p>This Order Code Covers The Welding Machine and All of The Equipments</p> <p>3000900037</p>	 <p>3020900154</p>	 <p>2020900647</p>	 <p>2020900648</p>	 <p>6051900088 (Optional)</p>
------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------------------------------