



- Suitable for all weldable materials and all types of current
- Precise and efficient TIG arc striking by high frequency
- Standard equipped with pulse mode integrated into the control with available "easy-pulse" facility
- Low energy consumption and high efficiency
- Automatic compensation for mains voltage fluctuations within + %15 - %20
- High performance on thin metal sheets
- Very good MMA welding characteristics with any type of electrodes
- Single - Phase network

Inverter



Welding Process		TIG	MMA
Input Voltage	V	1 Phase 50/60 Hz, 220 V	
Installed Power	kW	5.4	6.3
Fuse (delayed action)	A	16	16
No Load Voltage	V	100	100
Current Range	A	5-200	5-180
Duty Cycle at (40°C)	%100 %60 %30	140 / 180 / 220	120 / 150 / 180
Standards		EN 60974-1 / EN 60974-3 / EN 60974-10	
Protection Class	IP	23	
Insulation Class		H	
Dimensions (L*W*H)	mm	465 / 185 / 390	
Weight	kg	15.5	

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments

3021000014 Air Cooled	1021000008	6051900083	2020900723	1051300003	1024300005 (Optional)	2020900179 (Optional)	6051300053 (Optional)	6051300012 (Optional)