



- Fully functional, user-friendly control panel layout for easy setup of welding parameters.
- Digital ampermeter and voltmeter
- Generator compatible, ideal for site use.
- Can remotely control current .
- Built-in Fan-on-Demand (smart fan) reduces power consumption, fault rate and the intake of dust and fumes.
- Recessed controls and connections designed to eliminate damage.
- PoWer TIG 270-TP (Pulse) machine to adjust the arc concentrate, reduce distortion and increase travel speed.
- HF and Lift TIG ignition meeting all requirements.
- Optional remote control
- Suitable for stainless steel ,carbon steel, copper, titanium e.t.c welding.
- 2 year warranty - for labor and parts.

Extra Functions

MMA mode

Hot-Start/Arc-Force/Anti-stick (VRD(optional))

HF TIG/Lift-TIG mode

- Pre gas time/Post gas time/Up slope-Down slope time/Starting current/Ending current
- 2T/4T/Spot welding
- Base current / Peak current / Pulse duty cycle Pulse frequency

Protection and Design

- Thermal protection /Overcurrent and Overvoltage protection
- Plastic front and rear panel
- Durable metal body
- Lightweight and portable

Applications

- Industrial applications
- Industrial plants
- Maintenance and repair
- Pipe construction
- Shipbuilding
- Metal construction
- Aerospace industry
- Chemical industry
- Process and food industry



Input Voltage	V	3 Faz, 50/60 Hz, 380 V ±%10
Installed Power	kW	10
Delayed Fuse	A	16,5
No Load Voltage	V	77
Output Voltage Range	V	5-270
Duty Cycle at (40°C)	%100 %35	200 270
Standards		EN 60974-1 / EN 60974-10:2014
Protection	IP	21 S
Insulation Class		H
Dimensions (L*W*H)	mm	460 x 210 x 410
Weight	kg	18

STANDARD & OPTIONAL EQUIPMENTS

<p>This order code covers the welding machine and all of the equipments</p> <p>3021000131</p>	 <p>1021000107</p>	 <p>6051900083 (Gas Cooled)</p>	 <p>2020901327</p>	 <p>1051300003</p>
--	---	--	---	--