



**Inverter**

**Product Features**

- Maximum efficiency
- Able to operate with generators
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under  $\pm$  %20 voltage fluctuations
- With the help of Pulse Function
- High performance on ultra thin surfaces without deformation
- HF TIG/MMA/Lift TIG multi purpose ability

**Extra Functions**

**TIG**

- 2T/4T Trigger Mode Selection
- Pre-Post Gas Flow Time Selection
- Initial and finishing time
- Adjustable Pulse function

**MMA**

- Arc Force
- Hot Start
- Self diagnostic with the error code







**Usage Areas**

- Industrial Facilities
- Production of bicycles, fitness machines, stainless steel equipments
- Construction Areas
- Shipyards
- Maintenance & Repair Jobs
- Container Production
- Pipelines



Input Voltage (V)	Power Cons. (kVA)	No Load Voltage (V)	Welding Current Range (A)	Duty Cycle(40°)		Standards	Protection	Isolation Class	Dimensions (DxWxH) (mm)	Weight (kg)
				%100	%60					
3 Phase, 50/60 Hz, 380 V $\pm$ %15	16	77	5-315	244	315	EN ISO 60974-1 EN ISO 60974-10	IP23	H	605 x 330 x 565	49

**Standard & Optional Equipments**

<p>This order code covers the welding machine and all of the equipments (Gas Cooled)</p> <p><b>3021000065</b></p>	<p>This order code covers the welding machine and all of the equipments (Water Cooled)</p> <p><b>3021000066</b></p>	 <p><b>1021000042</b></p>	 <p><b>6051900083</b> (Gas Cooled) <b>6051900076</b> (Water Cooled)</p>	 <p><b>1051300003</b></p>	 <p><b>2020900649</b></p>	 <p><b>2020900066</b> (Optional)</p>	 <p><b>1024300007</b> (Optional)</p>
---	---	--	--	--	---	---	---

GEDİK Welding provides full support for after sales services. 1 year warranty.