



Inverter

- Especially designed for use under heavy working conditions
- Very good welding performance with tine adjustment control
- Suitable for long working conditions with %100 duty cycle
- Digital current and voltage setting display
- Suitable to work under ± 10 voltage fluctuations and constant welding current at high temperature
- Suitable for very long welding seams and very thick workpieces.
- Embedded expert program with 10 sets of complete welding parameters
- Uninfluenced by input voltage fluctuation
- Digital communication between tractor and welder
- 3 and 4 wheeled tractor unit (optional)
- Flux collecting unit
- The slides have the ability to move horizontally and vertically
- Smart fan feature greatly expands working life
- Self-diagnostic function with error code display
- Electro slag welding facility

Mode:

LIFT-TIG, MMA Welding,

Extra Functions:

- Hot Start
- Arc Force
- Wire diameter selection
- CC / CV selection
- Inductance setting



Input Voltage	V	3 phase, 50/60 Hz $\pm 10\%$, V
Installed Power	kW	75
Fuse (delayed action)	A	115
No Load Voltage	V	92
Current Range	A	60~1250
Duty Cycle at (40°C)	100%	1250
Standards		EN 60974-1 / EN 60974-5 / EN 60974-10
Protection Class	IP	23 S
Insulation Class		H
Dimensions (L*W*H)	mm	788 / 366 / 815
Weight	kg	105

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments								
	3021000100	1021000064	1020900004	1020900005 (Optional)	2020900686	6051900107 (Optional)	2020900879	105180000 15 mt