



- Maximum efficiency
- Able to operate with generators
- Designed for Heavy Industrial Use
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under \pm % 10 Energy fluctuations

TIG Mode

- Lift-TIG available

Extra Functions

- Hot Start
- Arc Force
- Anti Stick
- VRD Fonksiyonu

Protection Functions

- Thermal Protection
- Phase missing
- Overcurrent Protection
- Overvoltage Protection

Design

- Plastic front and rear panels
- Durable metal body
- Light weight



Input Voltage	V	3 Phase, 50/60 Hz, 380 V \pm %10
Installed Power	kW	22,8
Fuse (delayed action)	A	16
No Load Voltage	V	92
Current Range	A	20-400
Duty Cycle at (40°C)	%60 %100	400 / 300
Standards		EN IEC 60974-1 / EN IEC 60974-10
Protection Class	IP	21S
Insulation Class		H
Dimensions (L*W*H)	mm	485 / 240 / 445
Weight	kg	19

STANDARD & OPTIONAL EQUIPMENTS

This order code covers the welding machine and all of the equipments

3021000094



1021000059



2020900647



2020900648



6051900088 (Optional)

Perfect welding capability for all types of electrodes with \varnothing 2,0 - 5,0 mm diameter.