

Product Features

- Efficient use of every single inch with constant suction and filtration
- Easily traps and filters all kinds of fumes and volatile wastes with its high local extraction power
- Flexible and extendable extraction arms allow easy access
- Extraction arms of different lengths
- Features optional hepa filter
- Alerts to “clean the filter” when the air flow is insufficient
- Suitable for all welding processes with its durable and silent structure
- Its special design ensures maximum fire safety
- Operation lifetime ranging from 300 to 600 hours
- Fully consistent design with CE standards



General Filter Data

Filtering Phase	3-phase
Filter Type	Disposable
Filter Surface Area	16 m ²
Efficiency	>99%
Main Filter Surface	16 m ²
Main Filter Class	F8
Phase 1 Filter	Washable Spark Trap
Phase 2 Filter	Replaceable Pre-Filter G4
Phase 3 Filter	Replaceable Main Filter F8

Technical Details

Dimensions	650 x 750 x 1030 mm
Weight	105 kg (excluding arm)
Engine Output	1,1 kw
Power Supply	3 x 400 V/50 Hz
Noise Level	72 dB(A)
Current	2,7 A
Fan Type	Radial - Narrow Type With Rotor
Certification	CE
Main Filter Surface	~17 m ³
Extraction Capacity	1300 m ³ /h
Main Filter Class	F8

Standard and Optional Equipment

This order code includes the Main Unit and Standard 3m Arm / F8 and G4 Filters

605140022



2m 605140065
3m 605140066
4m 605140067



Main Filter (F8)
605140002



Preliminary Filter (G4)
605140028



Main Filter H13
605140033
(Opsiyonel)



Intermediary Filter F7
605140034
(Opsiyonel)