

Flux Cored Wire For Hardfacing HARDCOR 600 G

Standards

TS EN 14700	: T Fe 6
EN 14700	: T Fe 6
DIN 8555	: MF 6-GF-60 GP

Chemical Composition of		
Weld	Metal	(Typical)

С	Si	Mn	Cr	Fe
0.40	0.70	0.60	9.0	Rest

Mechanical Properties

Hardness (as welded) (HB)	
600	

Typical Base Material Grades

 Hardfacing of parts of earth and mineral mining machines, impact drilling and crushing devices, guide springs, edges of cutting tools, hard bucket edges and teeth, all of which are made of alloyed or unalloyed steels, as well as in other materials required to have high resistance to wear, debarking knives, agricultural tillage tools, earth moving bucket lips

Features and Applications

- · High resistance to wear and to impact
- · Alloy group is martensitic tool steel
- · Weld metals of high hardness and high tougness
- · Machinability of metal through grinding only
- It is excellent choice for components that are required to maintain a sharp edge
- Shielding Gas: CO2

Resistance Type and Level

Friction	High Temp.	Corrosive	Machining
Impact	Thermo Shock	Crack Resistance	

Operating Data

Diameter (mm)	Welding Current (A)	Voltage (V)	Stick-out (mm)
1.20	140 - 200	26.0 - 30.0	30.0 - 35.0
1.60	180 - 200	26.0 - 30.0	30.0 - 35.0

Current Type

FCAW / D.C. (+)

Operating Data

Product Code	Diameter x Length (mm) / (inch)		Package Weight (Kg)
3030500010	1.20	0.047"	15
3030500011	1.60	0.062"	15

Approvals: SEPRO