# Flux Cored Wire For Hardfacing **HARDCOR M 67**

#### **Standards**

TS EN 14700 : T Z Fe 16 EN 14700 : T Z Fe 16 DIN 8555 : MF 10 GF 65 G

# Chemical Composition of Weld Metal % (Typical)

С	Mn	Si	Cr	В
~2.00	0.5	0.5	7.5	4.5

#### **Mechanical Properties**

Hardness		
(As Welded) (HRC)		
65 - 67		

#### **Typical Base Material Grades**

 Repair of equipment used in mining and steel milis. Hardfacing equipment and tools used in the construction and agriculture industries, highway constructure equipment, conveyor chains, mixing paddles, cement pumps components, etc

#### **Features and Applications**

- Use with CO<sub>2</sub> and Ar-CO<sub>2</sub> mix possible
- The weld metal characteristics and structure is similar to hard chrome alloys
- Excellent resistance to abrasion from sand and minerals
- . The weld metal is machinable only by grinding
- Stringer bead technique is recommended
- The hardfacing contains check cracks, but this does not impair wear resistance

# **Resistance Type and Level**

Friction	High Temp.	Corrosive	Machining
Impact	Thermo Shock	Crack Resistance	

# **Operating Data**

Diameter	Welding Current	<b>Voltage</b>	Stick-out
(mm)	(A)	(V)	(mm)
1.60	180 - 350	25.0 - 32.0	20.0 - 25.0

# **Current Type**

FCAW / D.C. (+)

# **Operating Data**

Product	Diameter x Length		Package Weight
Code	(mm) / (inch)		(Kg)
3030500026	1.60	1/16	15

**Approvals: SEPRO**