



Product Characteristics

- Fume extracting welding table can be used for minor welding works, grinding and plasma cutting applications
- It can be used in any location due to their small size
- They offer the same homogenous extraction capacity in all areas
- Fume-extracting welding table are available in 1200mm and 1500mm sizes
- The extracted air first passes through a Preliminary Filter (G4), which retains the largest particles. The main filter guarantees effective cleaning with 99% efficiency
- Due to the light weight and mobility, it could easily be used in multiple locations.
- The low noise output ensures a comfortable working environment for the operators
- It achieves the $\geq 5 \mu$ retention required under the OHS law, with 99.9% efficiency

General Filter Data

Filtering Phase	3 phase
Filter Type	Disposable
Filter Surface Area	16m ²
Efficiency	>%99
Main Filter Surface	16m ²
Main Filter Class	H11
Phase 1 Filter	Washable Spark Holder
Phase 2 Filter	Replaceable Preliminary Filter (G4)
Phase 3 Filter	Replaceable Main Filter H11

Technical Details

Dimensions (WxDxH)	800x1030mm
Dimensions (D)	1200mm
Weight (excluding the arm)	125kg
Engine Output	1,5Kw
Noise Level	72dB(A)
Extraction Capacity	1300m ³ /h
Pressure Loss	2000Pa
Power Supply	3x400V / 50Hz

Standard and Optional Equipment



Main Filter (H11)
1000901985



Preliminary Filter (G4)
1000901213



Preliminary Filter
2020901333



KM1250 PRO
BOTTOM EXTRACTION WELDING TABLE
3020900191