



- Arc parameter electronic control for an excellent cutting quality
- Energy saving function to switch off the power source cooling fan when no longer necessary
- Cutting parameters stability within $\pm 10\%$ mains voltage fluctuations
- Long lasting consumable parts
- Innovative and user friendly design
- IP 23 protection class and dust-proof electronic components, thanks to the innovative. "Tunnel" fan cooling system, allow their use in the toughest work environment
- Electrode wearing and improper operation signalling
- Possibility of cutting grids and perforated lamination sheets
- Contact cutting possibility without sliding blocks or other spacers



PoWer CUT 75

Input Voltage	V	3 Phase 50/60 Hz, 400 V, ± 10
Installed Power	kVA	11
Fuse (delayed action)	A	16
Current Range	A	20-70
Cutting Capacity	mm	Severence: 25 / Quality: 20
Duty Cycle at (40°C)	%100 %60 %40	55 / 65 / 70
Standards		EN 60974-1 / IEC 60974-3 / EN 60974-7 / EN 60974-10 / S
Protection Class	IP	23 S
Insulation Class		H
Dimensions (L*W*H)	mm	595 / 185 / 390
Weight	kg	23

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments			
	3021000138	1021000105	1051900025
			2020900841

GEDİK Welding provides full support for after sales services. 1 year warranty.