



- Compact size and light weight
- Instantaneous arc starts and stable arc
- User friendly operations
- Cope with dust and sudden rain
- Light weight and compact size
- Automatic compensation for mains voltage fluctuations within $\pm 15\%$
- Perform very well in MMA welding
- 3 phase network
- Current increase and decrease by single / double clicking of the standard torch switch
- Pulse welding allows a better arc control and less deformation of the work piece (0,1-500 Hz)
- Personalised welding program starting and recoiling

Inverter



PoWer TIG 300 DC Pulse		TIG	MMA
Input Voltage	V	3 Phase 50/60 Hz, 400 V ± 15	
Installed Power	kVA	11	9
Fuse (delayed action)	A	32	32
Open Circuit Voltage	V	58	58
Current Range	A	4-300	10-250
Duty Cycle at (40°C)	%100	190	158
	%60	245	204
	%30	300	250
Standards	EN 60974-1 / EN 60974-3 / EN 60974-10		
Protection Class	IP	23 S	
Insulation Class	H		
Dimensions (L*W*H)	mm	640 / 250 / 370	
Weight	kg	30	

STANDARD & OPTIONAL EQUIPMENTS

This Order Code Covers The Welding Machine and All of The Equipments 3021000008 Air Cooled 3021000009 Water Cooled							
	1021000005	6051900083	2020900649	1051300003	2020900175 (Optional)	1024300000 (Optional)	6051900076 (Optional)

GEDİK Welding provides full support for after sales services. 1 year warranty.