



Inverter

Product Features

- Maximum efficiency
- Able to operate with generators
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under \pm %20 voltage fluctuations
- With the help of Pulse Function
- High performance on ultra thin surfaces without deformation
- HF TIG/MMA/Lift TIG multi purpose ability

Extra Functions

TIG


- 2T/4T Trigger Mode Selection
- Pre-Post Gas Flow Time Selection
- Initial and finishing time
- Adjustable Pulse function

MMA

- Arc Force
- Hot Start
- Self diagnostic with the error code







Usage Areas

- Industrial Facilities
- Production of bicycles, fitness machines, stainless steel equipments
- Construction Areas
- Shipyards
- Maintenance & Repair Jobs
- Container Production
- Pipelines



Input Voltage (V)	Power Cons. (kVA)	No Load Voltage (V)	Welding Current Range (A)	Duty Cycle(40°)		Standards	Protection	Isolation Class	Dimensions (DxWxH) (mm)	Weight (kg)
				%100	%60					
3 Phase, 50/60 Hz, 380 V \pm %15	16	77	5-315	244	315	EN ISO 60974-1 EN ISO 60974-10	IP23	H	605 x 330 x 565	49

Standard & Optional Equipments

<p>This order code covers the welding machine and all of the equipments (Gas Cooled)</p> <p>3021000065</p>	<p>This order code covers the welding machine and all of the equipments (Water Cooled)</p> <p>3021000066</p>	 <p>1021000042</p>	 <p>6051900083 (Gas Cooled) 6051900076 (Water Cooled)</p>	 <p>1051300003</p>	 <p>2020900649</p>	 <p>2020900066 (Optional)</p>	 <p>1024300007 (Optional)</p>
---	---	--	--	--	---	---	---

GEDİK Welding provides full support for after sales services. 1 year warranty.