



**Inverter**

**Product Features**

**Cellulose Mode**

- Extra Arc Force current ensure deep penetration and bring perfect vertical down-welding of cellulose electrodes. (CEL)
- Maximum efficiency
- Low energy consumption

**TIG Mode**

- Lift - TIG available

**Extra Functions**

- VRD - ON / OFF
- Anti stick
- Able to operate with generators
- Hot Start / Arc Force (included)

**Protection Functions**

- Thermal Protection
- Over-current Protection
- Over-voltage Protection

**Usage Areas**

- Shipyards
- Automotive Industry
- Chemical
- Machine Production
- Pipelines
- Boiler and pressure vessel manufacturing



Input Voltage (V)	Power Cons. (kVA)	Delayed Fuse (A)	No Load Voltage (V)	Welding Current Range (A)	Duty Cycle(40°)	Standards	Protection	Isolation Class	Dimensions (DxWxH) (mm)	Weight (kg)
					%35					
1 Phase, 50/60 Hz, 230 V ±%15	9	39	82	10-200	200	EN ISO 60974-1 EN ISO 60974-10	IP23S	F	381 x 155 x 298	7,3

**Standard & Optional Equipments**

This order code covers the welding machine and all of the equipments

3021000095



1021000060



2020900723



2020900724



6051900088 (Optional)

Perfect welding capability for all types of electrodes with Ø 2,0 - 4,0 mm diameter. GEDIK Welding provides full support for after sales services. 1 year warranty