



Product Features

Effective Working

- Maximum efficiency
- Able to operate with generators
- Designed for Heavy Industrial Use
- Adjusting the sensitivity of current with digital display
- Instant welding current measuring and monitoring
- Suitable to work under \pm % 10 Energy fluctuations

TIG Mode

- Lift-TIG available

Extra Functions

- Hot Start
- Arc Force
- Anti Stick
- VRD Fonksiyonu

Protection Functions

- Thermal Protection
- Phase missing
- Overcurrent Protection
- Overvoltage Protection

Design

- Plastic front and rear panels
- Durable metal body
- Light weight



Input Voltage (V)	Power Cons. (kVA)	Delayed Fuse (A)	No Load Voltage (V)	Welding Current Range (A)	Duty Cycle(40°)		Standards	Protection	Isolation Class	Dimensions (DxWxH) (mm)	Weight (kg)
					%100	%60					
3 Phase, 50/60 Hz, 380 V \pm %10	22,8	16	92	20-400	300	400	EN ISO 60974-1 EN ISO 60974-10	IP23	H	485 x 240 x 445	19

Standard & Optional Equipments

This order code covers the welding machine and all of the equipments

302100094



102100059



2020900647



2020900648



6051900088 (Optional)

Perfect welding capability for all types of electrodes with \varnothing 2,0 - 5,0 mm diameter. GEDİK WELDING provides full support for after sales services. 1 year warranty